


ThermaCool® TC3008

Elastomeric Gap Filler

Saint-Gobain® ThermaCool TC3008 is a high performance, soft ceramic-filled silicone elastomer typically supplied with a PET release liner on both sides. The product is intrinsically tacky and has excellent compression performance over a wide range of stack up tolerances with minimal force applied to component parts. TC3008 can be supplied with a fabric or film on one side for additional support during handling and assembly.



- Soft and compliant gap filler with excellent thermal performance
- Thermal conductivity = 3.0 W/m-K
- Integral support using fabric or PET film
- Fabric support provides good cut resistance for high abuse applications
- Low pressure applied to assembled components
- Provides high range thermal conductivity
- Cost effective gap filler solution for many high performance applications



APPLICATIONS

- · Power conversion equipment
- Telecommunications
- Consumer electronics
- Automotive electronics
- Thermal modules to heat sinks



ThermaCool TC3008 Elastomeric Gap Filler — Properties

Performance tests are run using standard test procedures. The values presented are typical values and should not be used for specification purposes.

| Property | TC3008 | Test Method |
|--|---------------------------------|-------------|
| Color | Light Blue | Visual |
| Total thickness, nominal (mm) (1) | 0.5~7.0 | ASTM D374 |
| Density (g/cc) | 2.85 | ASTM D792 |
| Hardness (Shore 00) | 65 | ASTM D2240 |
| Continuous Use Temp (°F) / (°C) | -65°F to 392°F / -54°C to 200°C | _ |
| 100 mil, 50% Deflection Force (psi) | 36 | _ |
| Electrical | | |
| Voltage Breakdown (VAC) | > 5000 | ASTM D149 |
| Volume resistivity (ohm-cm) | 3.5 × 10 ¹¹ | ASTM D257 |
| Flame Rating | V-0 | UL94 |
| Thermal | | |
| Thermal Impedance (°C in²/W) 100 mil (2) | 0.92 | ASTM D5470 |
| Thermal conductivity (W/m-K) | 3.0 | ASTM D5470 |

^{1) 0.5} mm increments. 2) Deflection 30% strain.

Data reflects non-supported option.

Shelf Life

12 months after the date of manufacture when stored in original packaging at temperatures up to 25°C and 50% relative humidity.



Saint-Gobain Tape Solutions

North America | South America | Europe | Asia For a full list of locations, please visit tapesolutions.saint-gobain.com/contact-us IMPORTANT: It is the user's responsibility to ensure the suitability and safety of Saint-Gobain products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. Saint-Gobain assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated.

WARRANTY: For a period of 6 months, Saint-Gobain warrants this product(s) to be free from defects in manufacturing. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. SAINT-GOBAIN DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Form #1059 | © Saint-Gobain January 2021 | ThermaCool is a trademark of Saint-Gobain.

^{*}All properties are typical values and should not be used for writing specifications.